

In-Line Optical Filter OFM-15


The OFM-15 is a compact and reliable bandpass filter module. It uses Santec's proven interference filter technology and quality manufacturing techniques to provide a high isolation with long-term reliability and minimum loss. A wide range of filters are available; narrow bandwidth filters for individual channel filtering of 50, 100 and 200GHz spaced system, wide bandwidth filters for C/L, Red/Blue, 1310/1550, and B-PON band separation, OSC Filters and ASE noise cut Filters.

Features


- ▶ Low passband flatness
- ▶ Compact size suitable for system integration
- ▶ Industry standard package
- ▶ Telcordia GR-1221 qualified
- ▶ RoHS compliant

Applications

- ▶ Specific band or group - channel filtering
- ▶ Noise clean-up filter
- ▶ ASE noise reduction in transmitter
- ▶ CATV, Access Networks
- ▶ The 50GHz Filter is suitable for Long Haul and METRO networks
- ▶ B-PON



Dimensions



Unit: mm

■ Performance

Parameter	Unit	
Center Wavelength	nm	1550 nm window, ITU grid wavelengths
Thermal Stability (typical)	nm/°C	≤ 0.001
Return Loss	dB	≥ 45
Polarization Dependent Loss (PDL)	dB	≤ 0.15
Polarization Mode Dispersion (PMD)	ps	≤ 0.1
Optical Power	dBm	23
Operating Temperature	°C	-5 to +70
Storage Temperature	°C	-40 to +85

■ 100 GHz Filter Specifications

Parameter	Unit	
Passband Width (-0.5dB Bandwidth)	nm	≥ ± 0.11
Flatness	dB	≤ 0.5
Insertion loss	dB	≤ 1.2
Adjacent Channel Isolation	dB	≥ 25
Non-adjacent channel isolation	dB	≥ 40

*1 All parameters are specified over operating temperature range.

*2 Insertion loss per filter includes Ripple and PDL, without connectors.

*3 Please contact Santec to discuss specific performance requirements.

■ Ordering Code

OFM-15-A-B-C-D/E

A: Channel : **1**: 1ch
 B: Type : **10A0**: 100GHz Add **10D0**: 100GHz Drop **20A0**: 200GHz Add
20D0: 200GHz Drop
 C: Fiber Length : **10**: 1.0m **20**: 2.0m
 D: Connector : **00**: No Connector **FS**: FC-SPC **FA**: FC-APC **SS**: SC-SPC
SA: SC-APC **MU**: MU-SPC **MJ**: MUJ-SPC **LC**: LC-SPC
 E: Center Wavelength : (ex) 1552.52nm --->1552.52

www.santec.com E-Mail : sales@santec.com

2005 © SANTEC CORPORATION Santec reserves the right to make changes in equipment design, components or specifications without notice.



SANTEC CORPORATION

5823 Ohkusa-Nenjyozaka, Komaki, Aichi 485-0802, Japan Tel. +81-568-79-1959 Fax +81-568-79-1718

SANTEC U.S.A. CORPORATION

433 Hackensack Ave., Hackensack, NJ, 07601, U.S.A. Toll Free +1-800-726-8321 (santec-1) Tel. +1-201-488-5505 Fax +1-201-488-7702

SANTEC EUROPE LIMITED

Magdalen Centre, Robert Robinson Ave., The Oxford Science Park, Oxford OX4 4GA, U.K. Tel. +44-1865-784960 Fax +44-1865-784961

SANTEC (SHANGHAI) Co., Ltd.

No.800 Zhangyang Road Changhang Tower, Pudong District, Shanghai 200122 China Tel: +86-21-58361261, +86-21-58361262 Fax: +86-21-58361263