


# MEMS Attenuator with PMF PM-MOVA

Our MEMS (Micro Electro Mechanical Systems) based attenuator is available in a range of specifications for any DWDM application and PM-MOVA is manufactured with PMF (Polarization Maintaining Fiber). Optical properties are excellent with good PER and wavelength dependence. Santec's tilting mirror design coupled with laser welded packaging ensures a reliable, stiction-free device.



## features

- ▶ Low loss, Low WDL
- ▶ Low Power Consumption
- ▶ Bright and Dark Type Available
- ▶ World Smallest Package Available (13mm length)
- ▶ Telcordia GR-1221 Qualified
- ▶ RoHS Compliant

## Specifications

Parameter	Unit		Spec	Note
Wavelength Range	-	nm	1530 to 1570	C band
			1570 to 1610	L band
Insertion Loss	Max.	dB	1.0	w/o connectors
Polarization Extinction Ratio	Min.	dB	15	All operating conditions
Max. Attenuation	Max.	dB	30	-
Response Time	Max.	msec	10	10-90%
Input Optical Power	Max.	dBm	25	-
Drive Voltage	Max.	V	20	-
Storage Temperature Range	-	degC	-40 to 85	Non condensation
Operating Temperature Range	-	degC	-5 to 70	Non condensation
Fiber Type	-	-	PMF	Fiber length : 1.0+/-0.1m

[www.santec.com](http://www.santec.com) E-Mail : [sales@santec.com](mailto:sales@santec.com)

2019 © SANTEC CORPORATION Santec reserves the right to make changes in equipment design, components or specifications without notice.



**SANTEC CORPORATION**  
5823 Ohkusa-Nenjozaka, Komaki, Aichi 485-0802, Japan Tel. +81-568-79-3536 Fax +81-568-79-1718

**SANTEC U.S.A. CORPORATION**  
433 Hackensack Ave., Hackensack, NJ 07601, U.S.A. Toll Free +1-800-726-8321(santec-1) Tel. +1-201-488-5505 Fax +1-201-488-7702

**SANTEC EUROPE LIMITED**  
Grand Union Studios, 332 Ladbrooke Grove, London W10 5AD, U.K. Tel. +44-20-3176-1550

**SANTEC (SHANGHAI) Co., Ltd.**  
11F Room E, Hua Du Bldg., No.838 Zhangyang Road, Pudong, Shanghai 200122 China Tel: +86-21-58361261, +86-21-58361262 Fax: +86-21-58361263